## **SIEMENS**

Data sheet 6XV1875-5LH50

## product type designation

product description

## antenna connection cable N-Connect/SMA plug/plug

Connecting cable for SIMATIC NET antennas, preassembled

N-Connect/SMA male/ male flexible connection cable pre-assembled, Length 5 m, flexible connecting cable SCALANCE M antenna.



suitability for use	Flexible connecting cable for connecting an antenna to SCALANCE M
wire length	5 m
electrical data	
number of electrical connections	2
type of electrical connection	N-Connect/SMA male/male
transmission frequency	0 6000 MHz
attenuation factor per length	
at 2.4 GHz / typical	0.53 dB/m
• at 5.2 GHz / typical	0.83 dB/m
• at 5.85 GHz / typical	0.89 dB/m
return loss	
• minimum	23 dB
impedance	
rated value	50 Ω
capacity per length / at 1 kHz	82 pF/m
relative speed	82 %
mechanical data	
design of the shield	Braided shield made of tin-plated copper wires
outer diameter	
of inner conductor	1.4 mm
• of dielectric	3.8 mm
of cable sheath	6.3 mm
symmetrical tolerance of the outer diameter / of cable sheath	0.2 mm
thickness / of cable sheath	3.76 mm
material	
of inner conductor	Cu
• of dielectric	polyethylene foam
of cable sheath	FRNC
color	
of cable sheath	pastel turquoise
bending radius	
<ul><li>with single bend / minimum permissible</li></ul>	32 mm
with multiple bends / minimum permissible	45 mm
tensile load / maximum	80 N
weight per length	75 kg/km
ambient conditions	
ambient temperature	
<ul> <li>during operation</li> </ul>	-40 +80 °C

during storage	-40 +80 °C
during transport	-40 +80 °C
during installation	-25 +80 °C
chemical resistance	
to mineral oil	conditional resistance
radiological resistance / to UV radiation	resistant
protection class IP	when plugged in
product features, product functions, product components / general	
product feature	
<ul><li>halogen-free</li></ul>	Yes
• silicon-free	Yes
standards, specifications, approvals	
certificate of suitability	
<ul> <li>EAC approval</li> </ul>	Yes
<ul> <li>RoHS conformity</li> </ul>	Yes
• fire protection in accordance with EN 45545-2	No
standard	
for fire behavior / flame resistance	UL 1685 (Vertical tray), UL 1581 Sec. 1090 (H)
reference code	
<ul> <li>according to IEC 81346-2</li> </ul>	WG
<ul> <li>according to IEC 81346-2:2019</li> </ul>	WGB
further information / internet links	
internet link	
<ul><li>to web page: SiePortal</li></ul>	https://sieportal.siemens.com/
<ul><li>to website: Image database</li></ul>	https://www.automation.siemens.com/bilddb
<ul> <li>to website: Industry Online Support</li> </ul>	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)
Approvals / Certificates	

**General Product Approval** 

Environment

Manufacturer Declara-tion







Confirmation

6/3/2024 last modified: